

Full HD IP Broadcast PTZ Camera **PTZ- X20-IP**

Capturing The Unreachable

The PTZ-X20-IP is one of AIDA's most well-rounded Full HD cameras yet. The camera features IP streaming technology by H.264 or the newer H.265 High Efficiency Video Coding (HEVC). With integrated RS232 and VISCA over IP camera control, this camera is compatible with most IP based controllers, simplifying existing workflows with better cable management. The camera features traditional multi video format outputs such as 3G-SDI, HDMI, USB 3.0, as well as on-line video outputs RTSP/RTMP. Our camera's cost effective approach makes professional grade PTZ cameras, at the fraction of the price.



KEY FEATURES:



APPLICATIONS:



LIVE PRODUCTION

WORSHIP

VIDEO CONFERENCE

EDUCATION

LIVE STREAMING

MAIN FEATURES

- Full HD Progressive Scan sensor captures sharp and vivid color.
- Advanced digital image processor provides vivid and detailed images with full access feature sets.
- Motion-compensated temporal noise reduction filter leads to effective noise reduction for motion video without blur.
- 3G/HD-SDI, HDMI, RJ-45, USB 3.0, and USB 2.0 for versatility and seamless video performance.
- Power Optical Zoom capability up to 20X.
- Compatible with other industry leading products, conforming with SMPTE 424M/292M standard.
- Auto White Balance and shutter speed provides the optimized performance in a variety of situations.
- Built-in OSD controls for customizable image settings.
- Versatile and compact.

SPECIFICATIONS

VIDEO		LENS	
Image Sensor	1/2.85" Progressive CMOS	Lens	20X HD Optical Zoom, F1.5 ~ F3.0
Effective Pixels	Horizontal: 1920, Vertical: 1080	PTZ	
Pixel Size	2.13 μm (H) x 2.13 μm (V)	Pan/Tilt Range	Pan: 340°, Tilt: +90 to -30°
Resolution	1080p & 1080i: 1920 x 1080	Pan/Tilt Speed	Pan: 0° to +120°/s, Tilt: 0° to +80°/s
Resolution Rate	1080 60p/59.94p/50p/30p/29.97p/25p 24p/23.98p 1080 60i/59.94i/50i 720 60p/59.94p/50p/30p/29.97p/25p	Presets	128 Positions
IP Rate	1920 x 1080 @ 1~60 1280 x 720 @ 1~60 1024 x 576 @ 1~60 620 x 360 @ 1~60	Field of View	61°
Output	HD-SDI/3G-SDI HDMI RJ45 USB 3.0 & 2.0	STANDARD	
Color Space	4:2:2 (YCbCr) 10bit	SMPTE	SMPTE 292M, SMPTE 424M
Min. Illumination	0.1Lux	IP Protocol	TCP/IP, RTSP/RTMP
FUNCTION		PHYSICAL	
White Balance	Auto, Manual, Auto Tracking, One Push, Indoor, Outdoor	Camera Control	Protocol: VISCA Interface: RS-232C IN & OUT, RJ-45 Remote Controller
Focus	Auto, Manual	Operation Temp	32°F - 104°F
Shutter Speed	1 to 1/10,000 Sec.	Dimension	155mm x 160mm x 170mm / 6.10" x 6.92" x 6.69"
		Weight	1.35kg / 2.97lbs
		Power	12VDC (+9 - +15VDC) PoE+

*Specification are subject to change without notice.

PACKAGE CONTENTS



Remote Controller



Camera Mounting Bracket



USB 3.0



Power Adapter & Cable

At **AIDA Imaging**, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters. From concept to reality, **AIDA Imaging** meticulously creates products that are applicable to various solutions, effective for the global user.