

UHD-100A

Launch your creations in Ultra-HD

Drive your visual inspirations with clarity. The UHD-100A simplifies the creation of video content that requires Ultra-HD quality, ranging from telemedicine to machine vision in its smallest form.



KEY FEATURES:









APPLICATIONS:









MEDICAL



LIVE PRODUCTION WORSHIP RACING

THEATER



MAIN FEATURES

- •4K UHD 1/2.5 Progressive Scan CMOS sensor captures sharp and vivid UHD video even under very low light conditions.
- Advanced digital imaging processor provides vivid and detailed images by utilizing Dynamic Range, Auto White Balance, and Noise Reduction.
- Superb motion-compensated temporal noise reduction filter for motion video without blurring.
- •OSD control breakout cable with power input and RS-485 for remote communication.
- •Interchangeable lens design compatible with CS and C mount lenses.
- Perfectly suited for broadcast, pro audio/video, and security.
- •Versatile, compact, and rugged design.
- •With TRS Stereo Audio Input for embedded audio over HDMI.

SPECIFICATIONS

VIDEO

1/2.5" Progressive CMOS **Image Sensor**

Diagonal 7.20mm **Sensor Size**

Horizontal: 3840, Vertical: 2160 **Effective Pixels Pixel Size** $1.62 \mu m$ (H) x $1.62 \mu m$ (V)

Resolution 4096 x 2160, 3840 x 2160, 1920 x 1080,

1280 x 720

Resolution Rate 2160 30p/29.97p/25p/24p

1080 60p/59.94p/50p/30p/

29.97p/25p/24p 1080 60i/59.94i/50i

720 60p/59.94p/50p/30p/25p

Output **HDMI 1.4**

Color Space 4:2:2 (YCbCr) 10bit

FUNCTION

White Balance AWB / AE / AF

Full Auto, Bright, Shutter Priority, **Exposure**

Iris Priority, Manual

Other WDR, DIS (Digital Image Stabilization), 2D/3D

> Noise Reduction, Digital Slow Shutter, Black Level Compensation, Flicker Detection

LENS Lens

C/CS Mount (Default UHD 3.2mm Lens)

AUDIO

3.5mm TRS Stereo Mic-in & Input

Line in over I/O Cable

16/24/32 Bits Sample Rate

PHYSICAL

Camera Control RS485

OSD Button

32°F - 104°F **Operation Temp**


Dimension 39mm x 39mm x 50.50mm /

1.53" x 1.53" x 1.99"

Weight 140g / 0.30lbs 12VDC (+9 - +15VDC) **Power**

*Specification are subject to change without notice.


PACKAGE CONTENTS



I/O Breakout Cable



DC 12v Power Supply & Sockets Adapter



3.2mm 12MP 4K Lens (Pre-installed)

At ADIA Imaging, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters.

From concept to reality, AIDA Imaging meticulously creates products that are applicable to various solutions, effective for the global user.