

POV CAMERA



HD-100A

Content Creation just got simpler and more Affordable

The HD-100A takes your vision and brings it to life in the content you create, whether you're capturing for education, faith, or social media. Explore your passion with the HD-100A



KEY FEATURES:



APPLICATIONS:




LIVE PRODUCTION



WORSHIP



RACING



EDUCATION



SECURITY



MAIN FEATURES


- Full HD Progressive Scan sensor captures sharp and vivid color under different light conditions.
- Advanced digital image processor provides vivid and detailed images by utilizing WDR, White Balance, and Noise Reduction.
- Motion-compensated temporal noise reduction filter leads to effective noise reduction for motion video without blur.
- HDMI seamless video performance.
- Black Level Set-up provides the better color transition from digital to analog.
- Auto White Balance and shutter speed provides the optimized performance in a variety of situations.
- Interchangeable lens design makes it compatible with auto-iris CS and C mount lenses.
- Built-in OSD controls for customizable image settings.
- Versatile, compact, and rugged design.
- With TRS Stereo Audio Input for embedded audio over HDMI.

SPECIFICATIONS


VIDEO		LENS	
Image Sensor	1/3 inch Progressive CMOS	Lens	C/CS Mount (Default 4mm HD Lens)
Sensor Size	Diagonal 7.2mm	AUDIO	
Effective Pixels	Horizontal: 1920, Vertical: 1080	Input	3.5mm TRS Stereo Mic-in & Line in over I/O Cable
Pixel Size	2.75 μm (H) x 2.75 μm (V)	Sample Rate	16/24/32 Bits
Resolution	1080p & 1080i: 1920 x 1080 720p & 720i: 1280 x 720	PHYSICAL	
Resolution Rate	1080 60p/59.94p/50p/30p/29.97p/25p/24p 1080 60i/59.94i/50i 720 60p/59.94p/50p	Camera Control	RS485 VISCA, OSD Button
Output	HDMI 1.3a	Operation Temp	32° F - 104° F
Color Space	4:2:2 (YCbCr) 10bit	Dimension	39mm x 39mm x 50.50mm / 1.53" x 1.53" x 1.99" (With default 4mm Lens)
Min. Illumination	0.2Lux (Day), 0.1Lux (Night), 0.005Lux (Slow Shutter ON)	Weight	180g / 0.39lbs (With default 4mm Lens)
White Balance	Auto & Manual (9,000 K - 11,000 K)	Power	6W at 12VDC (+9 - +15VDC)

**Specification are subject to change without notice.*


PACKAGE CONTENTS



I/O Breakout Cable



DC 12v Power Supply & Sockets Adapter




4mm Megapixels Lens (Pre-Installed)



USB Cable



C-Mount Cap Adapter



Sensor Cap

At **AIDA Imaging**, innovation is key to crafting our tried and tested quality imaging solutions. We strive to raise the bar by engineering and manufacturing cutting edge cameras and converters. From concept to reality, **AIDA Imaging** meticulously creates products that are applicable to various solutions, effective for the global user.